

Adhesives & Epoxies Product Selection Matrix



	Waterproofing	Crack Isolation		Adhesives			Epoxies		Grouts				
	B-6000	Flex-Guard	Speed-Flex	B-4050	B-2000	B-1000	B-7000 Epoxy Mortar & Grout	B-150 Epoxy Adhesive	Unsanded Grout 800	Sanded Grout 700			
DESCRIPTION	Latex polymer based product used as a waterproofing membrane or as part of a crack isolation system	Primerless, pressure sensitive, elastomeric, crack isolation, and anti-fracture system	Primerless, pressure sensitive, elastomeric, crack isolation, and anti-fracture system	Premium pre-mixed adhesive offering outstanding slip resistance	Pre-mixed adhesive	Pre-mixed adhesive	Three-part, 100% solid, chemical resistant and water cleanable tile setting and grouting epoxy	Two-part, 100% solid, acid and alkali resistant tile setting epoxy	Portland cement based grout for joints up to 1/8"	Portland cement based grout for joints from 1/16" to 1/2"			
COLOR	Purple (wet); maroon (dry)	White	White	White	White	White	38 colors	Tan	38 colors	38 colors			
SPECIAL ADDITIVES / CHARACTERISTICS	Meets IAPMO standards for shower pans	Extra Heavy Service Rating	Extra Heavy Service Rating	Micro Defense® for mold and mildew resistance	Micro Defense® for mold and mildew resistance	Micro Defense® for mold and mildew resistance	100% solids	100% solids	Micro Defense® for mold and mildew resistance	Micro Defense® for mold and mildew resistance			
ANSI STANDARDS	ANSI A118.10 & A118.12	ANSI A118.12	ANSI A118.12	ANSI A136.1 Type I & II	ANSI A136.1 Type I & II	ANSI A136.1 Type I & II	ANSI A118.3	ANSI A118.3	ANSI A118.6	ANSI A118.6 & A118.7			
INSTALLS WHERE Interior/Exterior Walls, Floors, Ceilings	INTERIOR / EXTERIOR Walls, Floors & Ceilings	INTERIOR / EXTERIOR	INTERIOR	INTERIOR Walls & Floors	INTERIOR Walls & Floors	INTERIOR Walls & Floors	INTERIOR / EXTERIOR* Walls & Floors	INTERIOR / EXTERIOR Walls & Floors	INTERIOR / EXTERIOR Walls, Floors & Ceilings	INTERIOR / EXTERIOR Walls, Floors & Ceilings			
INSTALLS/USED WITH	N/A	N/A	N/A										
Cement tile													
Ceramic tile							•	•	•	•	•	•	•
Cork underlayment							•	•	•				
Glass tile													
Granite countertops										•	•		
Hardened steel													
Marble										•	•	•	•
Mosaic tile							•	•	•	•	•	•	•
Natural stone (flat backed)							•	•	•	•	•	•	•
Pavers										•	•	•	•
Porcelain tile							•	•	•	•	•	•	•
Quarry Tile				•	•	•	•	•	•	•			
Slate							•	•		•			
INSTALLS OVER WHAT SUBSTRATE									N/A	N/A			
Concrete	•	•	•	•	•	•	•	•					
Countertops	•			•	•	•	•	•					
Exterior Grade Plywood (interior only)	•	•	•	•	•	•	•	•					
Gypsum wall board	•			•	•	•	•	•					
Hardwood floors		•	•										
Masonry	•			•	•	•	•	•					
OSB	•	•	•										
Plaster	•			•	•	•							
Tile backerboard	•	•	•	•	•	•	•	•					
Tile over tile	•	•	•				•	•					
Vinyl / vinyl asbestos flooring	•	•	•				•	•					
QUALIFYING SYSTEM WARRANTY	Lifetime, 10-year, 5-year	Lifetime	30-year	n/a	n/a	n/a	Lifetime, 10-year, 5-year	n/a	Lifetime, 10-year, 5-year	Lifetime, 10-year, 5-year			
TOTAL ELIGIBLE LEED POINTS**	3 points	3 points	3 points	2 points	2 points	2 points	2 points	2 points	3 points	3 points			
Regional Materials (MR 5.1 & MR 5.2)	2 points	2 points	2 points	1 point	1 point	1 point	1 point	1 point	2 points	2 points			
Low-emitting Materials (EQ 4.1)	1 point	1 point	1 point	1 point	1 point	1 point	1 point	1 point	1 point	1 point			

* When used outdoors as a grout, the color may change with UV exposure.

NOTE: It is the responsibility of the installer/appliator to ensure the suitability of the product for its intended use and to ensure that all substrates are properly prepared. For additional information, please visit www.prospec.com or contact ProSpec Technical Services. All installations must conform to ANSI A108.5 specification and the Tile Council of North America handbook.