



# EPOXY HAZE REMOVER

## Description

ProSpec® Epoxy Haze Remover is an effective aid for use in the final cleanup of a ceramic installation. Ideal for removal of epoxy grout haze and urethane and latex films.

## Features

- Removes the film left by epoxy grouts
- Epoxy haze can be removed even after several months
- Interior or exterior use
- Cleans ceramic porcelain, slate and quarry tile
- Contains no abrasive or harsh chemicals

## Technical Data

### Appearance

Straw colored

### Weight per Gallon

8.55 lbs.

### Flash Point

196° F (92° C)

### Solubility in Water

Miscible

### Odor

Mild

## Application

Allow new grout to cure for 24 hours before using.

**NOTE:** Wear rubber or plastic gloves when using this product.

**Spot Treatment:** Apply Epoxy Haze Remover to the surface of individual tiles with a paintbrush. Allow to remain for 20-30 minutes and check for softening of cured film. Leave on tile until film loosens easily. Remove using a stiff bristled brush (not steel/wire) or coarse nylon-scrubbing pad.

**Entire Floor Treatment:** Pour a ribbon of Epoxy Haze Remover on the floor and spread liberally with a lamb's wool applicator. Apply to an area about 3 feet wide to avoid stepping in solution when machine scrubbing. Check for softening of epoxy film after 15 minutes and every 5 minutes thereafter. Agitate with a stiff bristle brush. Remove Epoxy Haze Remover immediately when film becomes soft. This will have the least effect on the grout joints.



# EPOXY HAZE REMOVER

## Packaging

1 Gallon (3.8 L), 6 per case

## VOC Content

0.09 lbs./gallon or 10.4 g/l

## Caution

KEEP OUT OF REACH OF CHILDREN AND ANIMALS.

CONTAINS N-METHYL PYRROLIDONE AND N-BUTOXY PROPANOL. SKIN AND EYE IRRITANT. Avoid prolonged or repeated contact with skin. Do not take internally.

## First Aid

For eyes, flush immediately with plenty of water for at least 15 minutes. If irritation develops, see a doctor immediately. For skin,

wash thoroughly with soap and water. If irritation persists, see a doctor. If too much is inhaled, move to fresh air. If swallowed,

drink large amounts of water. Induce vomiting. See a doctor immediately.

LIMITED 1 YEAR WARRANTY FROM DATE OF MANUFACTURE: Bonsal American warrants that this product and the materials used therein meet or exceed the applicable standards listed and enforced at the time of manufacture. Bonsal American will replace any product or part which proves defective due to quality of ingredients used or due to the manufacturing process itself. This Warranty shall apply only if the product is used in strict accordance with applicable specifications and instructions provided by Bonsal American for its use, and Bonsal American shall not be liable otherwise. Replacement of any defective product, or, at Bonsal American's option, refund of the purchase of any defective product shall be the buyer's sole remedy under this Warranty, and Bonsal American shall in no event be liable for any damages in excess of the purchase price of the defective product. BONSAL AMERICAN SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL OR SPECIAL DAMAGES INCLUDING LOSS OF PROFITS OF ANY KIND. Product demonstrations are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. This Warranty constitutes the sole warranty given by Bonsal American in connection with this product. No modification of this Warranty in favor of any buyer shall be valid unless given in writing and signed by an officer of Bonsal American. Bonsal American has authorized no person to make or give any other warranties or representation, oral or written on its behalf. IN PARTICULAR, THERE ARE NO IMPLIED WARRANTIES, INCLUDING WITHOUT EXCEPTION WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

ProSpec® is the registered trademark of Bonsal American, Inc.  
8201 Arrowridge Blvd. Charlotte, NC 28273 • www.prospec.com • E-Mail: prospec@oldcastleap.com