

Rebar Coat
Acrylic Additive
B-730 Mortar Additive
B-6000 Waterproof Membrane/Crack Isolation Membrane

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name 1. Rebar Coat
2. Acrylic Additive
3. B-730 Mortar Additive
4. B-6000 Waterproof Membrane/Crack Isolation Membrane

Product Use: Various.

Manufacturer/Supplier: Bonsal American, Inc.
8201 Arrowridge Blvd.
Charlotte, NC
28273

Phone Number: (800) 334-0784 Tech Service 8:00 to 5:00 Eastern, Mon.-Fri.

Emergency Phone: CHEMTREC 800-424-9300
INTERNATIONAL + 01- 703-527-3887

Date of Preparation: April 29, 2009

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: May cause eye irritation.

Skin: May cause skin irritation.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Medical Conditions Aggravated By Exposure: Asthma. Allergies.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

This product is a hazardous chemical as defined by NOM-018-STPS-2000.

Rebar Coat
Acrylic Additive
B-730 Mortar Additive

B-6000 Waterproof Membrane/Crack Isolation Membrane

Potential Environmental Effects: No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

| Ingredient | UN Number | H / F / R / Special* | CAS # | Wt. % |
|------------|-----------|------------------------------|-------|-------|
| | | None by WHMIS/OSHA criteria. | | |

* Per NOM-018-STPS-2000

Section 4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

Skin Contact: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Not flammable by WHMIS/OSHA criteria.

Means of Extinguishing:

- Suitable Extinguishing Media:** Treat for surrounding material.
- Unsuitable Extinguishing Media:** Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

- Sensitivity to Mechanical Impact:** Not available.
- Sensitivity to Static Discharge:** Not available.

Protection of Firefighters: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental Precautions: If large quantities enter a waterway, advise local authorities.

Methods for Containment: Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Rebar Coat
Acrylic Additive
B-730 Mortar Additive

B-6000 Waterproof Membrane/Crack Isolation Membrane

Methods for Clean-Up: Vacuum or sweep material and place in a disposal container.

Other Information: Not available.

Section 7: HANDLING AND STORAGE

Handling:

Avoid contact with skin and eyes. Do not swallow. Good housekeeping is important to prevent accumulation of dust. Avoid generating and breathing dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Store in dust-tight, dry, labeled containers. Keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers. Use corrosion-resistant structural materials and lighting and ventilation systems in the storage area.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

| Ingredient | Exposure Limits | |
|------------|-----------------|-----------|
| | OSHA-PEL | ACGIH-TLV |
| | Not applicable. | |

Engineering Controls: When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear approved eye (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-------------------------|-----------------|
| Appearance: | Powder. |
| Color: | Various. |
| Odour: | Characteristic. |
| Odour Threshold: | Not available. |
| Physical State: | Powder. |
| pH: | Not available. |
| Viscosity: | Not available. |

Rebar Coat
 Acrylic Additive
 B-730 Mortar Additive
 B-6000 Waterproof Membrane/Crack Isolation Membrane

| | |
|---|---|
| Freezing Point: | Not available. |
| Boiling Point: | Not available. |
| Flash Point: | Not available. |
| Evaporation Rate: | Not available. |
| Lower Flammability Limit: | Not available. |
| Upper Flammability Limit: | Not available. |
| Vapor Pressure: | Not available. |
| Vapor Density: | Not available. |
| Specific Gravity: | Not available. |
| Solubility in Water: | Not available. |
| Coefficient of Water/Oil Distribution: | Not available. |
| Auto-ignition Temperature: | Not available. |
| Percent Volatile, wt. %: | Not available. |
| VOC content, wt. %: | 42.7 g/L Acrylic Additive 42.7 g/L B-730 Mortar Additive 11 g/L B-6000 Waterproof Membrane/Crack Isolation Membrane 11g/L Rebar Coat |

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Keep dry in storage.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: None known.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

| Ingredient | IDLH | LD ₅₀ (oral) | LC ₅₀ |
|--------------------|--|-------------------------|------------------|
| | Not applicable. | | |
| Eye: | May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. | | |
| Skin: | May cause skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. | | |
| Ingestion: | May be harmful if swallowed. May cause stomach distress, nausea or vomiting. | | |
| Inhalation: | May cause respiratory tract irritation. | | |

Rebar Coat
Acrylic Additive
B-730 Mortar Additive
B-6000 Waterproof Membrane/Crack Isolation Membrane

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: Not hazardous by WHMIS/OSHA criteria.

Carcinogenicity: Not hazardous by WHMIS/OSHA criteria.

Ingredient

Chemical Listed as Carcinogen or Potential Carcinogen *

Not applicable.

* See Section 15 for more information.

Mutagenicity: Not hazardous by WHMIS/OSHA criteria.

Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Not hazardous by WHMIS/OSHA criteria.

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Classification

Not regulated

TDG Classification

Not regulated

NOM-004-SCT2-1994 Classification

Not regulated

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the

PRO SPEC MATERIAL SAFETY DATA SHEET Pro Spec® 020

Rebar Coat
Acrylic Additive
B-730 Mortar Additive

B-6000 Waterproof Membrane/Crack Isolation Membrane

Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

Mexico: MSDS prepared pursuant to NOM-018-STPS-2000.

SARA Title III

| | | | | |
|-------------------|---|--|-----------------------------|------------------------|
| Ingredient | Section 302 (EHS) TPQ (lbs.) | Section 304 EHS RQ (lbs.) | CERCLA RQ (lbs.) | Section 313 |
| | Not applicable. | | | |

State Regulations

California Proposition 65:

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

| | | |
|-------------------|----------------------------|---------------------|
| Ingredient | Canada DSL/NDSL | USA TSCA |
|-------------------|----------------------------|---------------------|

All ingredients are on DSL/NDSL & TSCA inventories.

HMIS - Hazardous Materials Identification System

Health - 0 Flammability - 0 Physical Hazard - 0

NFPA - National Fire Protection Association:


Health - 0 Fire - 0 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

Not controlled.

Mexico Classification:



Blue = Health Red = Flammability Yellow = Reactivity White = Special

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

- A1 - Confirmed human carcinogen.
- A2 - Suspected human carcinogen.
- A3 - Animal carcinogen.
- A4 - Not classifiable as a human carcinogen.
- A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

- 1 - The agent (mixture) is carcinogenic to humans.
- 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

Rebar Coat

Acrylic Additive

B-730 Mortar Additive

B-6000 Waterproof Membrane/Crack Isolation Membrane

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

| |
|--------------------------------------|
| Section 16: OTHER INFORMATION |
|--------------------------------------|

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: April 29, 2012

Version #: 1.0

Prepared by: Nexreg Compliance Inc.
Phone: (519) 488-5126
www.nexreg.com