

# PRO SPEC<sup>®</sup> MATERIAL SAFETY DATA SHEET Pro Spec<sup>®</sup> 028

B-4050 Multi-Purpose Adhesive AXAPTA 201131 & 201130 LAWSON 65464532 & 65464531

B-2000 Wall & Floor Adhesive AXAPTA 201126 & 201125 LAWSON 65464522 & 65464521

B 1000 Mastic Adhesive AXAPTA 201100 LAWSON 65464511

## Section 1: PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name &amp; Number</b>	1. B-4050 Multi-Purpose Adhesive Product Number: AXAPTA 201131 & 201130 LAWSON 65464532 & 65464531
	2. B-2000 Wall & Floor Adhesive Product Number: AXAPTA 201126 & 201125 LAWSON 65464522 & 65464521
	3. B 1000 Mastic Adhesive Product Number: AXAPTA 201100 LAWSON 65464511
<b>Product Use:</b>	Adhesive.
<b>Manufacturer/Supplier:</b>	Bonsal American, Inc. 8201 Arrowridge Blvd. Charlotte, NC 28273
<b>Phone Number:</b>	800-334-0784 Tech Service 8:00 to 5:00 Eastern, Mon.-Fri.
<b>Emergency Phone:</b>	CHEMTREC 800-424-9300 INTERNATIONAL + 01-703-527-3887
<b>Date of Preparation:</b>	September 10, 2009

## Section 2: HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

CAUTION

HARMFUL BY INHALATION IRRITATING TO EYES. IRRITATING TO SKIN. HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.

**Potential Health Effects:** See Section 11 for more information.

**Likely Routes of Exposure:** Skin contact, eye contact, inhalation, and ingestion.

**Eye:** Irritating to eyes.

**Skin:** Irritating to skin.

**Ingestion:** May be harmful if swallowed. May cause stomach distress, nausea or vomiting. Harmful: may cause lung damage if swallowed.

**Inhalation:** Harmful by inhalation. May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis.

**Chronic Effects:** Prolonged or repeated contact may dry skin and cause irritation.

**Signs and Symptoms:** Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. Vapours may cause drowsiness and dizziness.

**Medical Conditions Aggravated By Exposure:** Because of its irritating properties, product may aggravate preexisting skin, eye, and respiratory conditions.

**Target Organs:** Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# PRO SPEC<sup>®</sup> MATERIAL SAFETY DATA SHEET Pro Spec<sup>®</sup> 028

B-4050 Multi-Purpose Adhesive AXAPTA 201131 & 201130 LAWSON 65464532 & 65464531

B-2000 Wall & Floor Adhesive AXAPTA 201126 & 201125 LAWSON 65464522 & 65464521

B 1000 Mastic Adhesive AXAPTA 201100 LAWSON 65464511

This product is a hazardous chemical as defined by NOM-018-STPS-2000.

**Potential Environmental Effects:** No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful. See Section 12 for more information.

## Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	UN Number	H / F / R / Special*	CAS #	Wt. %
Stoddard solvent	UN1268	Not available.	8052-41-3	1-5
1,2,4-Trimethylbenzene	UN1993	Not available.	95-63-6	0.1-1
Silica, crystalline, quartz	Not available.	Not available.	14808-60-7	0.1-1
Ethylene glycol	Not available.	1/1/0	107-21-1	1-5

\* Per NOM-018-STPS-2000

## Section 4: FIRST AID MEASURES

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

**Skin Contact:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

**Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

**General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

**Note to Physicians:** Symptoms may not appear immediately.

## Section 5: FIRE FIGHTING MEASURES

**Flammability:** Not flammable by WHMIS/OSHA criteria.

### Means of Extinguishing:

**Suitable Extinguishing Media:** Treat for surrounding material.

**Unsuitable Extinguishing Media:** Not available.

**Products of Combustion:** May include, and are not limited to: oxides of carbon.

### Explosion Data:

**Sensitivity to Mechanical Impact:** Not available.

**Sensitivity to Static Discharge:** Not available.

**Protection of Firefighters:** Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## Section 6: ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental Precautions:** If large quantities enter a waterway, advise local authorities.

# PRO SPEC<sup>®</sup> MATERIAL SAFETY DATA SHEET Pro Spec<sup>®</sup> 028

B-4050 Multi-Purpose Adhesive AXAPTA 201131 & 201130 LAWSON 65464532 & 65464531

B-2000 Wall & Floor Adhesive AXAPTA 201126 & 201125 LAWSON 65464522 & 65464521

B 1000 Mastic Adhesive AXAPTA 201100 LAWSON 65464511

**Methods for Containment:** Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

**Methods for Clean-Up:** Scoop up material and place in a disposal container.

**Other Information:** Not available.

## Section 7: HANDLING AND STORAGE

### Handling:

Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

### Storage:

Keep out of the reach of children. Keep container tightly closed.

## Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Stoddard solvent	100 ppm	100 ppm
1,2,4-Trimethylbenzene	Not available. ((10 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (resp)); ((30 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (total));	25 ppm
Silica, crystalline, quartz	((250)/(%SiO <sub>2</sub> +5) mppcf TWA (resp))	0.025 mg/m <sup>3</sup>
Ethylene glycol	Not available.	50 ppm

**Engineering Controls:** When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits.

### Personal Protective Equipment:

**Eye/Face Protection:** Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

**Hand Protection:** Wear suitable gloves.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

**General Hygiene Considerations:** Handle according to established industrial hygiene and safety practices.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Paste-like compound.

**Color:** White.

**Odour:** Characteristic.

**Odour Threshold:** Not available.

**Physical State:** Solid.

# PRO SPEC<sup>®</sup> MATERIAL SAFETY DATA SHEET Pro Spec<sup>®</sup> 028

B-4050 Multi-Purpose Adhesive AXAPTA 201131 & 201130 LAWSON 65464532 & 65464531

B-2000 Wall & Floor Adhesive AXAPTA 201126 & 201125 LAWSON 65464522 & 65464521

B 1000 Mastic Adhesive AXAPTA 201100 LAWSON 65464511

<b>pH:</b>	Not available.
<b>Viscosity:</b>	Not available.
<b>Freezing Point:</b>	Not available.
<b>Boiling Point:</b>	Not available.
<b>Flash Point:</b>	Not available.
<b>Evaporation Rate:</b>	Not available.
<b>Lower Flammability Limit:</b>	Not available.
<b>Upper Flammability Limit:</b>	Not available.
<b>Vapor Pressure:</b>	Not available.
<b>Vapor Density:</b>	Not available.
<b>Specific Gravity:</b>	Not available.
<b>Solubility in Water:</b>	Not available.
<b>Coefficient of Water/Oil Distribution:</b>	Not available.
<b>Auto-ignition Temperature:</b>	Not available.
<b>Percent Volatile, wt. %:</b>	Not available.
<b>VOC content, wt. %:</b>	0%, Not applicable; 0 wt, Not applicable.

## Section 10: STABILITY AND REACTIVITY

**Stability:** Stable under normal storage conditions. Keep dry in storage.

**Conditions of Reactivity:** Heat. Incompatible materials.

**Incompatible Materials:** None known.

**Hazardous Decomposition Products:** May include, and are not limited to: oxides of carbon.

**Possibility of Hazardous Reactions:** No dangerous reaction known under conditions of normal use.

## Section 11: TOXICOLOGY INFORMATION

### EFFECTS OF ACUTE EXPOSURE

#### Component Analysis

<b>Ingredient</b>	<b>IDLH</b>	<b>LD<sub>50</sub> (oral)</b>	<b>LC<sub>50</sub></b>
Stoddard solvent	20,000 mg/m <sup>3</sup>	> 5000 mg/kg, rat	> 5500 mg/m <sup>3</sup> 4hr, rat
1,2,4-Trimethylbenzene	Not available	5000 mg/kg, rat	18000 mg/m <sup>3</sup> 4 hrs, rat
Silica, crystalline, quartz	Not available	500 mg/kg, rat	Not available.
Ethylene glycol	Not available	4700 mg/kg, rat	> 200 mg/m <sup>3</sup> 4hr, rat

**Eye:** Irritating to eyes. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

**Skin:** Irritating to skin. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.

**Ingestion:** May be harmful if swallowed. May cause stomach distress, nausea or vomiting. Harmful: may cause lung damage if swallowed.

# PRO SPEC<sup>®</sup> MATERIAL SAFETY DATA SHEET Pro Spec<sup>®</sup> 028

B-4050 Multi-Purpose Adhesive AXAPTA 201131 & 201130 LAWSON 65464532 & 65464531

B-2000 Wall & Floor Adhesive AXAPTA 201126 & 201125 LAWSON 65464522 & 65464521

B 1000 Mastic Adhesive AXAPTA 201100 LAWSON 65464511

**Inhalation:** Harmful by inhalation. May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis. Vapours may cause drowsiness and dizziness.

## EFFECTS OF CHRONIC EXPOSURE

**Target Organs:** Lungs.

**Chronic Effects:** Hazardous by WHMIS/OSHA criteria.

Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.

**Carcinogenicity:** Hazardous by WHMIS/OSHA criteria.

## Ingredient

## Chemical Listed as Carcinogen or Potential Carcinogen \*

Stoddard solvent

Not listed.

1,2,4-Trimethylbenzene

Not listed.

Silica, crystalline, quartz

G-A2, I-1, N-1, CP65

Ethylene glycol

Not listed.

\* See Section 15 for more information.

**Mutagenicity:** Not hazardous by WHMIS/OSHA criteria.

**Reproductive Effects:** Not hazardous by WHMIS/OSHA criteria.

## Developmental Effects:

**Teratogenicity:** Hazardous by WHMIS/OSHA criteria.

**Embryotoxicity:** Hazardous by WHMIS/OSHA criteria.

**Respiratory Sensitization:** Not hazardous by WHMIS/OSHA criteria.

**Skin Sensitization:** Not hazardous by WHMIS/OSHA criteria.

**Toxicologically Synergistic Materials:** Not available.

## Section 12: ECOLOGICAL INFORMATION

**Ecotoxicity:** No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.

**Persistence / Degradability:** Not available.

**Bioaccumulation / Accumulation:** Not available.

**Mobility in Environment:** Not available.

## Section 13: DISPOSAL CONSIDERATIONS

### Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

# PRO SPEC<sup>®</sup> MATERIAL SAFETY DATA SHEET Pro Spec<sup>®</sup> 028

B-4050 Multi-Purpose Adhesive AXAPTA 201131 & 201130 LAWSON 65464532 & 65464531

B-2000 Wall & Floor Adhesive AXAPTA 201126 & 201125 LAWSON 65464522 & 65464521

B 1000 Mastic Adhesive AXAPTA 201100 LAWSON 65464511

## Section 14: TRANSPORTATION INFORMATION

### DOT Classification

Not regulated

### TDG Classification

Not regulated

### NOM-004-SCT2-1994 Classification

Not regulated

## Section 15: REGULATORY INFORMATION

### Federal Regulations

**Canadian:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**US:** MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

**Mexico:** MSDS prepared pursuant to NOM-018-STPS-2000.

### SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Stoddard solvent	Not listed.	Not listed.	Not listed.	Not listed.
1,2,4-Trimethylbenzene	Not listed.	Not listed.	Not listed.	Yes.
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
Ethylene glycol	Not listed.	Not listed.	5,000	Yes.

### State Regulations

#### California Proposition 65:

This product contains a chemical known to the state of California to cause cancer.

### Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
Stoddard solvent	DSL	Yes.
1,2,4-Trimethylbenzene	DSL	Yes.
Silica, crystalline, quartz	DSL	Yes.
Ethylene glycol	DSL	Yes.

### HMIS - Hazardous Materials Identification System

Health - 2\*      Flammability - 0      Physical Hazard - 0

### NFPA - National Fire Protection Association:

Health - 2      Fire - 0      Reactivity - 0

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

### WHMIS Classification(s):

- Class D2A - Carcinogenicity
- Class D2A - Teratogenicity and Embryotoxicity
- Class D2A - Chronic Toxic Effects
- Class D2B - Skin/Eye Irritant

# PRO SPEC<sup>®</sup> MATERIAL SAFETY DATA SHEET Pro Spec<sup>®</sup> 028

B-4050 Multi-Purpose Adhesive AXAPTA 201131 & 201130 LAWSON 65464532 & 65464531


B-2000 Wall & Floor Adhesive AXAPTA 201126 & 201125 LAWSON 65464522 & 65464521

B 1000 Mastic Adhesive AXAPTA 201100 LAWSON 65464511

## WHMIS Hazard Symbols:



## Mexico Classification:



**Blue = Health   Red = Flammability   Yellow = Reactivity   White = Special**

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

## SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

**OSHA (O)** Occupational Safety and Health Administration.

**ACGIH (G)** American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

**IARC (I)** International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

**NTP (N)** National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

## Section 16: OTHER INFORMATION

### Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

**Expiry Date:** September 10, 2012

**Version #:** 1.0

**Prepared by:** Nexreg Compliance Inc.

Phone: (519) 488-5126

[www.nexreg.com](http://www.nexreg.com)